



## REFLO\* SYNTHETIC 68A LOW TEMPERATURE AMMONIA REFRIGERATION COMPRESSOR FLUID

### Introduction

Petro-Canada's REFLO\* SYNTHETIC 68A is a full synthetic polyalphaolefin/alkyl benzene based ammonia refrigeration compressor fluid used in industrial refrigeration systems. REFLO SYNTHETIC 68A is formulated to outperform solvent refined paraffinic and naphthenic refrigerant oils by extending service life while significantly reducing operating costs. REFLO SYNTHETIC 68A is specifically formulated to outperform straight polyalphaolefin refrigeration compressor fluids by offering better seal performance, while maintaining excellent control over foaming and deposit formations. The result is a refrigeration compressor fluid that offers reliable, long-term performance with significant operational cost savings.

### Superior Performance Benefits

- **Extreme low temperature performance**
  - REFLO SYNTHETIC 68A is completely wax free and can operate at temperatures well below conventional mineral oils.
  - Excellent operation at low evaporator temperatures.
  - None of the wax deposit problems associated with paraffinics when used at very low temperatures.
- **Lower oil volatility reduces fluid consumption and maintenance costs**
  - Significantly less volatile than solvent refined paraffinics or naphthenics at high temperatures
  - Results in less oil carryover to the refrigeration system's low temperature side
  - Lower oil carryover also reduces plugging and deposit formation in evaporators, lowering maintenance costs
- **Lower solubility in ammonia improves system efficiency and performance**
  - REFLO SYNTHETIC 68A is less soluble in ammonia refrigerant than solvent refined paraffinics and Naphthenics
  - Less ammonia is absorbed into the compressor fluid, which can reduce gas entrainment in separator tanks and increase system efficiency
  - Lower concentrations of ammonia in the fluid allows it to maintain viscosity, so it lubricates better, reducing wear
  - Less compressor fluid is absorbed into the ammonia, reducing the potential for fluid to block piping, valves and filters
  - Lower concentration of compressor fluid in the ammonia also helps to maintain refrigerant purity, improving system efficiency and performance
- **Superior thermal and oxidation stability extends fluid life, reducing maintenance costs and downtime**
  - Resistance to oxidative and thermal breakdown guards against oil thickening, deposit and sludge formation
  - Helps to keep the compressor, heat exchanger and expansion valves operating at their design efficiency and performance standards
  - Extends fluid life, even in the presence of impurities in the ammonia refrigerant, saving on downtime and change-out costs

## **Additional Performance Benefits**

- High viscosity index ensures proper lubrication and protection from wear over a wide range of operating temperatures
- High flash point ensures safe operation at elevated temperatures
- Excellent seal, paint and plastic compatibility.

## **Applications**

REFLO SYNTHETIC 68A is formulated to lubricate ammonia refrigeration compressors used in large commercial operations such as cold stores, marine systems and food processing plants; specifically blast freezers that have very low evaporator temperatures. REFLO SYNTHETIC 68A is also used in manufacturing industries that require very low temperature control, such as pharmaceuticals and microelectronics. REFLO SYNTHETIC 68A can be used in ammonia refrigeration systems where evaporator temperatures are greater than -51°C / -60°F.

REFLO SYNTHETIC 68A is compatible with mineral oils such as hydro treated (HT) and solvent refined (SR) paraffinics as well as naphthenics. It may be used to top-up systems using these types of fluids. The full benefits of REFLO SYNTHETIC 68A will not be realized without a complete fluid change-out.

REFLO SYNTHETIC 68A is formulated to have good compatibility with seal materials; it contains a seal swell agent to protect against fluid leaks especially when naphthenic oils were used previously on the compressors. REFLO SYNTHETIC 68A is compatible with materials such as NBR, FKM, SBR, CR, NR, MVQ.

## Typical Performance Data

<b>PROPERTY</b>	<b>ASTM Test Method</b>	<b>DIN Test Method</b>	<b>REFLO Synthetic 68A</b>
Density, kg/L @ 15°C	D4052	-	0.841
Viscosity, cSt @ 40°C			61.8
cSt @ 100°C	D445		8.89
SUV @ 100°F	D2161		318
SUV @ 210°F	D2161		56.2
Viscosity Index	D2270		119
Pour Point, °C/°F	D0097	51597	-54 / -65
Flash Point, °C/°F	D0092	51376	245 / 473
Foam Characteristics, ml			
Sequence 1			0 / 0
Sequence 2	D0892	51566	10 / 0
Sequence 3			0 / 0
Total Acid Number (TAN), mg KOH/g	D0664	51558	<0.1
Specific Heat, Calories/g/°C, 38°C	-	-	0.4723
BTU/lb, 100°F	-	-	0.4723

The values quoted above are typical of normal production. They do not constitute a specification.

## Health and Safety

To obtain Material Health and Safety Data Sheets, contact one of Petro-Canada's TechData Info Lines.

## TechData Info Lines

If you would like to know more about Petro-Canada REFLO SYNTHETIC 68A or any other product in our complete line of quality lubricants, please contact us at:

### Lubricants Head Office

**Petro-Canada**  
2310 Lakeshore Road West  
Mississauga, Ontario  
Canada L5J 1K2



**Canada - West** . . . . . Phone 1-800-661-1199  
**- East (English)** . . . . . Phone 1-800-268-5850  
**(French)** . . . . . Phone 1-800-576-1686  
**Other Areas** . . . . . Phone (416) 730-2408  
**E-mail** . . . . . lubecsr@petro-canada.ca  
**Internet** . . . . . www.petro-canada.com

**Petro-Canada Europe Lubricants**  
**The Manor, Haseley Business Centre**  
**Warwick, Warwickshire**  
**CV35 7LS**  
**United Kingdom**

Phone . . . . . +44 (0) 2476-247294  
Fax . . . . . +44 (0) 2476-247295

**Petro-Canada America Lubricants**  
**980 North Michigan Avenue**  
**Suite 1400, #1431**  
**Chicago, Illinois**  
**USA 60611**

Phone . . . . . 1-888-284-4572  
Fax . . . . . (708) 246-8994  
E-mail . . . . . email@petro-canadaamerica.com